

Four-Way Valve / Air Pressure Valve

Sanitary Valves

Working Temp. -10°C~130°C

Actuator Manual

Seal Material PTEE

Body Material 316L

Connection Clamp Joint

SurfaceFinish Ra≤1µm


Indicator Line grooved on handle shows connected status when covered


Application User friendly for chromato graphic system



Four-Way Valve

No.	Α	В	Н	L1	L2	
1507199-000050	9.4	25	63	137.4	80	
1507199-000775	7.75	25	63	137.4	80	
1507199-000100	22.1	50.4	107	224.0	150	
	OEM/ODM	25	63	137.4	80	






Air Pressure Valve

- ·Adapt to products exposed to the air.
- ·To support seal stopper by pressing spring.
- Supreme seal o-ring with EPDM material.
- ·To press spring with opening pin & nut.
- Applying 316L material for.
- ·To fix body with clamp for user-friendly.
- ·Ventilation opening, spring is reset to close the design can be applied to CIP system.
- Suitable for evacuation of tank, tubing and other related equipments.

Air Pressure Valve

SIZE	L1	L2	D1	D2	
1/2"	30.0	36.2	50.4	26.0	





Phone :86-21-52762825
Email :sales@pvsflowcontrol.com
Address :Floor2, Building D1,
No.578, Lane1588,Zhuguang RD,
Qingpu District,Shanghai,201702